



# L Series Jaw Couplings



L Series Couplings use Sintered Iron Jaws for maximum strength & flexibility of bore size.



## Dimensions (mm)

Coupling Size	Type	Coupling Half									Insert Part Nos.					
		Min Bore	Max Bore	Setscrews	A	B	C	D	E	Weight kg	Buna-N	Urethane	Hytrell	Weight kg	Bronze	Weight kg
L035	1	-	9.5	-	15.9	20.6	7.2	6.7	-	.010	L035N	N/A	N/A	.002	N/A	-
L050	1	6	15.0	M5	27.4	43.7	11.9	15.9	-	.065	L050N	N/A	L050H	.007	L050B	.022
L070	1	9	19.0	M6	34.5	50.8	12.7	19.1	-	.135	L070N	L070U	L070H	.008	L070B	.028
L075	1	9	22.2	M6	44.5	54.0	12.7	20.6	-	.23	L075N	L075U	L075H	.012	L075B	.065
L090	1	9	25.4	M6	53.6	54.0	12.7	20.6	-	.36	L090N	L090U	L090H	.015	L090B	.100
L095	1	9	28.6	2xM6	53.6	63.5	12.7	25.4	-	.40	L090N	L090U	L090H	.015	L090B	.100
L099	1	12	30.2	2xM8	64.3	73.0	19.1	27.0	-	.61	L099N	L099U	L099H	.033	L099B	.150
L100	1	12	35.0	2xM8	64.3	89.0	19.1	34.9	-	.81	L099N	L099U	L099H	.033	L099B	.150
L110	1	15	41.3	2xM10	84.2	108.0	22.2	42.9	-	1.71	L110N	L110U	L110H	.065	L110B	.30
L150	1	15	47.6	2xM10	95.0	114.5	25.4	44.5	-	2.28	L150N	L150U	L150H	.095	L150B	.63
L190	2	20	54.0	2xM12	102.0	133.5	25.4	54.0	114.5	3.72	L190N	L190U	L190H	.145	L190B	.90
L225	2	20	60.0	2xM12	108.0	152.0	25.4	63.5	127.0	5.20	L225N	L225U	L225H	.190	L225B	1.12

Hytrell is a registered trademark of E.I. Dupont Nermours & Co.

## kW Power Ratings L Series Couplings

Refer to page 2 for standard selection procedure.

Insert Material	Coupling Size	Max Bore	Max rpm	Max Torque Nm	kW Power Capacities								
					50	100	300	600	900	1200	1500	1800	3600
BUNA-N	L035	9.5	31000	0.4	.002	.004	.013	.026	.037	.05	.06	.07	.15
	L050	16.0	18000	2.9	.015	.030	.092	.186	.276	.36	.45	.55	1.10
	L070	19.0	14000	5.0	.026	.052	.157	.313	.470	.63	.78	.94	1.88
	L075	22.2	11000	10.0	.052	.104	.285	.565	.940	1.24	1.56	1.88	3.76
	L090	25.4	9000	16.4	.086	.172	.515	1.03	1.54	2.06	2.57	3.09	6.18
	L095	28.6	9000	21.4	.112	.224	.670	1.35	2.02	2.68	3.35	4.03	8.05
	L099	30.2	7000	35.6	.190	.373	1.12	2.24	3.35	4.50	5.6	6.70	13.4
	L100	35.0	7000	47.0	.250	.500	1.48	2.95	4.40	5.90	7.4	8.90	17.7
	L110	41.3	5000	89.0	.470	.930	2.80	5.60	8.40	11.2	14.0	16.8	33.6
	L150	47.6	5000	142.4	.750	1.45	4.45	8.95	13.4	17.9	22.4	26.9	53.7
	L190	54.0	5000	192.3	1.00	2.01	6.05	12.1	18.1	24.2	30.2	36.2	72.5
L225	60.0	4200	263.5	1.38	2.76	8.30	16.5	24.8	33.0	41.3	49.6	99.0	
URETHANE	L050	16.0	18000	4.8	.03	.06	.16	.31	.48	.61	0.73	0.91	1.9
	L070	19.0	14000	7.5	.04	.08	.24	.47	.71	.94	1.17	1.41	2.8
	L075	22.2	11000	15.0	.08	.16	.47	.94	1.41	1.88	2.35	2.82	5.6
	L090	25.4	9000	24.5	.13	.26	.78	1.55	2.32	3.09	3.86	4.63	9.2
	L095	28.6	9000	32.0	.17	.34	1.01	2.01	3.02	4.03	5.03	6.04	12.1
	L099	30.2	7000	53.5	.28	.56	1.68	3.36	5.04	6.70	8.35	10.0	20.1
	L100	35.0	7000	70.5	.37	.74	2.21	4.42	6.65	8.87	11.1	13.3	26.5
	L110	41.3	5000	133.5	.70	1.40	4.20	8.40	12.6	16.8	21.0	25.2	50.0
	L150	47.6	5000	214.0	1.12	2.24	6.71	13.4	20.1	26.8	33.5	40.2	80.5
	L190	54.0	5000	288.5	1.51	3.02	9.10	18.1	27.2	36.2	45.3	54.4	108.8
L225	60.0	4200	395.0	2.07	4.14	12.40	24.8	37.3	49.7	62.1	74.5	149.0	
HYTREL® & BRONZE*	L050	16.0	18000*	5.7	.03	.06	.18	.36	.54	.72	.90	1.08	2.1
	L070	19.0	14000*	12.8	.07	.13	.40	.80	1.32	1.61	2.02	2.42	4.8
	L075	22.2	11000*	25.6	.14	.28	.80	1.60	2.40	3.20	4.00	4.80	9.7
	L090	25.4	9000*	44.2	.23	.46	1.39	2.77	4.16	5.55	6.95	8.35	16.6
	L095	28.6	9000*	64.0	.33	.67	2.00	4.00	6.05	8.05	10.1	12.1	24.1
	L099	30.2	7000*	89.0	.47	.93	2.80	5.60	8.40	11.2	14.0	16.8	33.5
	L100	35.0	7000*	128.1	.67	1.34	4.03	8.05	12.0	16.1	20.1	24.2	48.3
	L110	41.3	5000*	256.0	1.34	2.68	8.05	16.1	24.1	32.2	40.2	48.3	96.6
	L150	47.6	5000*	419.0	2.19	4.38	13.10	26.3	39.5	52.6	65.7	78.9	157.0
	L190	54.0	5000*	529.0	2.78	5.54	16.60	33.2	49.9	66.5	83.1	99.7	200.0
L225	60.0	4200*	712.0	3.75	7.50	22.50	45.0	67.5	90.0	112.5	135.0	270.0	

\*Note couplings with bronze inserts are limited to 250 rpm.

Tel: +44 121 360 0155

Fax: +44 121 325 1079

Email: sales@crossmorse.com