



	Total	Power	Signals	L	Weight(kg)
		15A	2A		IP51 IP65
SVTSC 05-x-A-06/00	6	6	-	45	0,7 1,4
SVTSC 05-x-A-00/12	12	-	12	45	0,7 1,4
SVTSC 05-x-A-12/00	12	12	-	69	1 2
SVTSC 05-x-A-06/12	18	6	12	69	1 2
SVTSC 05-x-A-00/24	24	-	24	69	1 2
SVTSC 05-x-A-18/00	18	18	-	93	1,2 2,5
SVTSC 05-x-A-12/12	24	12	12	93	1,2 2,5
SVTSC 05-x-A-06/24	30	6	24	93	1,2 2,5
SVTSC 05-x-A-00/36	36	-	36	93	1,2 2,5
SVTSC 05-x-A-24/00	24	24	-	117	1,5 3,1
SVTSC 05-x-A-18/12	30	18	12	117	1,5 3,1
SVTSC 05-x-A-12/24	36	12	24	117	1,5 3,1
SVTSC 05-x-A-06/36	42	6	36	117	1,5 3,1
SVTSC 05-x-A-00/48	48	-	48	117	1,5 3,1

	Power Rings	Signal Rings
Current	15A	2A
Voltage	600Vac/600Vdc	240Vac/240Vdc
Leads AWG	14	26
Contact material	Precious metals	Precious metals
Dielectric strength	1500VAC@60Hz,60s	500VAC@60Hz,60s
Insulation resistance	≥1000MΩ/500VDC	≥500MΩ/500VDC
Leads	tinning PTFE	
Dynamic contact resistance	<100mΩ @6Vdc 50mA 5RPM	
Suggested Speed	600RPM	
Temperature	-20°C~+80°C (ET option -40°C~+80°C)	
Housing material	engineering plastic*	
Protection degree	IP51*	
Bearings	steel ball bearings	

*Note: For IP65 option L=L+20mm and Ø54,5mm - Housing material aluminum alloy

version Änderung / changes

serV Drive Z.Nr. 00374

SVTSC 05

Die oben genannten Bemessungen sind Richtwerte.
Alle Abmessungen in mm / All dimensions in mm

Date : 27.02.2017
Author : Peter Uher