

P6 MAXILUBE®

AIR OPERATED GREASING SYSTEM (P6-01)

10 Year Warranty

*conditions apply

PRODUCT OVERVIEW

The P6 MAXILUBE™ is a premium quality, reliable, 50:1 air-operated greasing system that is excellent for high volume grease users that have many applications and require continuous high pressure greasing.

This portable grease dispensing system is suitable for 55kg pails and is equipped with a low air consumption motor that doesn't need to be lubricated due to the use of modern polymer materials.

Users will save on power and the oily mist and mess associated with air operated equipment is gone.

Suitable for underground coal mine applications.

FEATURES & BENEFITS

50:1 Ratio Air Motor
Delivers up to 460g/min for fast, efficient greasing. Instant delivery of up to 50 times applied air pressure

B2 Booster Gun
Boosts pressure up to 10,000psi to clear blocked grease nipples

KY Supergrip Coupler
Positive no-leak connection ensures grease reaches the bearing

360° ZSB Swivel
Improves manoeuvrability and offers easier one-handed operation

Fully Repairable
Provides a much longer service life



Quiet Air Motor Design
Meets all industry noise level standards. Doesn't require air-line lubricator. Zinc components suitable for underground mining applications.

Fixed Lid With Handles
Accommodates 55kg (or similar size) grease pails and prevents grease contamination

Rubber-Edged Follower Plate
Wipes container clean & prevents air pockets & contamination

Fully Sealed With Grease Strainer
Delivers clean contamination free grease to the application

4m High Pressure Grease Hose
Allows access to hard to reach applications

TECHNICAL SPECIFICATIONS

P6001 (50:1) Air-operated pump
4m x 6mm ID delivery hose
Compatible with 55kg (or similar size) pails
Grease viscosity up to NLGI No.2
Output 460g/min (at pump)
Maximum pump output pressure: 51,700kPa (7,500psi)
Maximum gun output pressure: 68,900kPa (10,000psi)
Maximum air pressure: 150psi
Minimum air pressure: 60psi
Pump inlet/outlet: 1/4" NPT (F)
Minimum compressor size: 0.08m ³ /min (3cfm)

OPTIONAL ACCESSORIES

PACKAGE INCLUDES

P6001 pump unit
Lid & rubber edged follower plate
4m high pressure hose
B2 booster gun
KY Supergrip coupler
ZSB high pressure swivel
Instruction manual

For more information visit www.macnaught.com.au/p6-01

MACNAUGHT Pty Ltd
41-49 Henderson Street
Turrella, NSW, 2205
Australia

T +61 2 9567 0401
F +61 2 9597 7773
E info@macnaught.com.au
W www.macnaught.com.au

MACNAUGHT USA Inc
614 South Ware Boulevard
Tampa, Florida, 33619
United States

T +1813 628 5506
F +1509 694 8495
E info@macnaughtusa.com
W www.macnaughtusa.com